



- STANDARD -
Specifications

Lift Model	Evergreen Standard
Special features	Energy saving VVVF controller. Built-in Rescue Device during power interruptions.
Type	Passenger
Speed	0.50 metres/second.
Capacity	Upto 6 passengers - 408 kgs. (max.).
Number of floors	Maximum of 5 floors.
Control	Down collective.
Drive	Microprocessor-based VVVF.
Car	MS steel (baked enamel paintwork) / prelaminated board. PVC flooring.
Car doors	Manually operated: MS folding shutter with MS gate /MS collapsible gate.
Landing doors	Manually operated: MS folding shutter with MS gate /MS collapsible gate.
Power supply	Single-phase, 230 volts AC. Built-in voltage stabilizer to function even upto 180 volts. Can be run on portable generator.
Other features	Automatic bilingual door open voice annunciator. Car fan and light. Battery operated emergency alarm and light. Direction and position indicators in Car and Landings.

Evergreen Standard car sizes

Passengers	Liftwell size (in mm)	Car size (in mm)
6	1600 x 1400	1200 x 940
6	1800 x 1250	1400 x 800
5	1600 x 1250	1200 x 800
4	1500 x 1150	1100 x 700

Clear opening	
MS folding shutter:	750 X 2000 mm.
MS collapsible gate:	800 x 2000 mm.
Minimum head room:	3800 mm.
Minimum lift pit depth:	1350 mm after plastering.
Machine room height:	2000 mm.